


Solenoid Valves (High Pressure R-410A)

- ✳ Suitable for, R-22, R-134A, R-404, R-410A
- ✳ Wide operating range of -40° - 105°C
- ✳ High maximum operating Pd to 31bar
- ✳ Din plug connection
- ✳ Certified UL ,VDE, CQC

Solder Solenoid Valves



SKY Part No.	Item Description	Length mm	Height mm	CV	Liquid Kw R-134A	R-407c	R-404a
705-04	1/4" SOL SOLENOID VALVE	102	82	0.32	5	5.4	3.8
705-06	3/8" SOL SOLENOID VALVE	111	88	0.93	14.8	16.1	11.2
705-08	1/2" SOL SOLENOID VALVE	127	95	2.2	35.3	38.2	26.7
705-10	5/8" SOL SOLENOID VALVE	176	100	3	48.3	52.3	36.5
705-14	7/8" SOL SOLENOID VALVE	191	117	5.8	48.3	52.3	36.5
705-18	1 1/8" SOL SOLENOID VALVE	191	117	6.9	92	94	70
705-22	1 3/8" SOL SOLENOID VALVE	280	144	10	196	152	197
705-26	1 5/8" SOL SOLENOID VALVE	281	144	15	297	302	225
705-34	2 1/8" SOL SOLENOID VALVE	281	152	25	468	472	531

Flare Solenoid Valves

SKY Part No.	Item Description	Length mm	Height mm	CV	Liquid Kw R-134A	R-407c	R-404a
706-04	1/4" MF SOLENOID VALVE	59	82	0.32	5	5.4	3.8
706-06	3/8" MFSOLENOID VALVE	69	88	0.93	14.8	16.1	11.2
706-08	1/2" MF SOLENOID VALVE	92	96	2.2	35.3	38.2	26.7
706-10	5/8" MF SOLENOID VALVE	104	104	3	48.3	52.3	36.5

Solenoid Valve Coils

SKY Part No.	Item Description	Frequency Hz	IP Rating
707-240	AC 240V SOLENOID COIL	50/60	65
707-24	AC 24V SOLENOID COIL	50/60	65

Solenoid Magnet



SKY Part No.	Item Description
800-1	Solenoid Magnet

